



US009411203B2

(12) **United States Patent**
Kimura et al.

(10) **Patent No.:** **US 9,411,203 B2**
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **SEMICONDUCTOR DEVICE AND DISPLAY DEVICE**

(75) Inventors: **Hajime Kimura**, Kanagawa (JP);
Shunpei Yamazaki, Tokyo (JP)

(73) Assignee: **Semiconductor Energy Laboratory Co., Ltd.** (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 563 days.

(21) Appl. No.: **13/600,658**

(22) Filed: **Aug. 31, 2012**

(65) **Prior Publication Data**

US 2013/0027282 A1 Jan. 31, 2013

Related U.S. Application Data

(63) Continuation of application No. 12/765,084, filed on Apr. 22, 2010, now Pat. No. 8,259,463, which is a continuation of application No. 11/405,327, filed on Apr. 17, 2006, now Pat. No. 7,710,739.

(30) **Foreign Application Priority Data**

Apr. 28, 2005 (JP) 2005-133741

(51) **Int. Cl.**
H05K 1/00 (2006.01)
G02F 1/1345 (2006.01)
G09G 3/20 (2006.01)

(Continued)

(52) **U.S. Cl.**
CPC **G02F 1/13452** (2013.01); **G09G 3/20** (2013.01); **H05K 3/361** (2013.01); **G09G 2300/0426** (2013.01); **H01L 2924/0002** (2013.01); **H05K 1/0263** (2013.01); **H05K 1/0265** (2013.01); **H05K 1/117** (2013.01); **H05K 2201/094** (2013.01); **H05K 2201/09727** (2013.01)

(58) **Field of Classification Search**

USPC 349/149–151
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,753,820 A 6/1988 Cusack
5,067,042 A 11/1991 Nagano

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0 971 564 A2 1/2000
EP 1 176 457 A2 1/2002

(Continued)

OTHER PUBLICATIONS

Hosono, H. et al., “Working Hypothesis to Explore Novel Wide Band Gap Electrically Conducting Amorphous Oxides and Examples,” *Journal of Non-Crystalline Solids*, vol. 198-200, 1996, pp. 165-169.

(Continued)

Primary Examiner — Tuan T Dinh

(74) *Attorney, Agent, or Firm* — Husch Blackwell LLP

(57) **ABSTRACT**

An object of the present invention is to decrease the resistance of a power supply line, to suppress a voltage drop in the power supply line, and to prevent defective display. A connection terminal portion includes a plurality of connection terminals. The plurality of connection terminals is provided with a plurality of connection pads which is part of the connection terminal. The plurality of connection pads includes a first connection pad and a second connection pad having a line width different from that of the first connection pad. Pitches between the plurality of connection pads are equal to each other.

13 Claims, 80 Drawing Sheets

